



MS6720 provides retailers with omnidirectional scanning performance in an ergonomic hand-held design that facilitates scanning of larger items otherwise unable to be presented to fixed position countertop scanners.

FEATURES

- Combination hand-held and fixed projection scanner
- Decodes all standard 1D bar codes
- Fully automatic scanning operation
- Stationary or adjustable stand available
- Concentrated omnidirectional scan pattern

Model MS6750 Only

- Decodes all standard 1D, RSS-14, RSS Limited and RSS expanded bar codes



MS6720 Quick Specs

Depth of Field:	0 mm - 203 mm (0" - 8") for 0.33 mm (13 mil) bar codes at default setting
Width of Field:	50.8 mm (2") @ face; 178 mm (7") @ 203 mm (8")
Scan Speed:	1000 scan lines per second
Scan Pattern:	5 fields of 4 parallel lines (omnidirectional)
Minimum Bar Width:	0.145 mm (5.7 mil)
Dimensions:	Height: 219 mm (8.6") Depth handle: 28 mm (1.1") Width handle: 48 mm (1 head: 75 mm (2.9") Width head: 77 mm (3")
System Interfaces:	PC Keyboard Wedge, RS232, OCIA, Light Pen Emulation, IBM 468X/469X Alone Keyboard
Light Source:	Visible Laser Diode 650 nm \pm 10 nm
Weight:	380 g (13.4 oz)
Shock:	Shock Designed to withstand 1 m (3.1') drops